

DECLARATION OF PERFORMANCE

SI-FS103050LL1010-003



1. Unique identification code of the product-type:	FIBRANxps 500-L		
2. Type, batch or serial number:	FS103050LL1010		
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification as foreseen by the manufacturer:	Thermal Insulation for Buildings (THiB) XPS-EN13164-T1-CS(10Y)500-DS(70,90)-DLT(2)5-TR400-WL(T)0,7-WD(V)3-FTCD1-MJ150		
4. Name and contact address of the manufacturer	FIBRAN d.o.o. Novo mesto Ko evarjeva ulica 1 SI-8000 Novo mesto, Slovenija www.fibran.si		
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:	AVCP - System 3		
7. Name and identification number of notified body	FIW No 751		
9. Essential characteristic - (EN13164:2012+A1:2015)	Symbol	Performance	
nominal width	bN [mm]	600	
nominal length	lN [mm]	1250	
thickness	dN [mm]	30	
Dimensional tolerances	T	1	
Compressive strength	CS(10Y) [kPa]	500	
Tensile strength perpendicular to faces	TR [kPa]	400	
Reaction to fire	Euro-class	E	
Continuous glowing combustion		NPD	
Acoustic absorption index		NPD	
water permeability	long term water absorption by total immersion	WL(T) [vol. %]	0,7
	long term water absorption by diffusion	WD(V) [vol. %]	3
Water vapor transmission	water vapor diffusion resistance factor	MJ	150
Durability of compressive strength against ageing/degradation	compressive creep	CC (2/1,5/50) [kPa]	NPD
Durability of thermal resistance against heat, weathering, ageing/degradation	declared thermal conductivity Lambda	D [W/m.K]	0,032
	declared thermal resistance	RD [m ² .K/W]	0,90
	freeze-thaw resistance after long term water diffusion test	FTCD	1
	freeze/thaw resistance after long term water absorption by total immersion	FTCI	NPD
	dimensional stability under specified temperature and humidity conditions	DS	(70,90)
	Deformation under specified compressive load and temperature conditions	DLT	(2)5
dangerous substances	Release of dangerous substances to the indoor environment	GWP<5; ODP 0; HFC free	
durability of reaction to fire against heat, weathering, ageing/degradation	The reaction to fire performance of XPS does not change with time.		
10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.			

Signed for and on behalf of the manufacturer by
Novo mesto, 17.05.2022

Jure Lovšin
Product Manager

HBCD free
'NPD' (No Performance Determined)